



# E-Flo™ Plus

## ELECTRIC CIRCULATING PUMPS

### Technical Specifications

Pump	E-Flo 4000	E-Flo 3000	E-Flo 2000
Max Fluid Pressure	250 psi (17 bar)	330 psi (23 bar)	460 psi (32 bar)
Flow at 20 cpm	22.6 gpm (85.5 lpm)	16.2 gpm (61 lpm)	12 gpm (45 lpm)
Volume per Cycle	144.6 oz (4278 cc)	105 oz (3070 cc)	76.5 oz (2263 cc)
Inlet/Outlet	2 inch Tri-Clamp	2 inch Tri-Clamp	2 inch Tri-Clamp
Weight	550 lb (250 kg)	540 lb (245 kg)	516 lb (234 kg)


### Dimensions



PROVEN QUALITY. LEADING TECHNOLOGY.

Springer Pumps, LLC

# Ordering Information



Power	Style	Motor	Sensor Circuit	Lower Size
E = Electric	P = Pump	0 = No Motor 1 = 230/400V ATEX 2 = 240/480V	0 = None 1 = Installed	1 = 1000 cc 2 = 1500 cc 3 = 2000 cc 4 = 1000 cc Maxlife 5 = 1500 cc Maxlife 6 = 2000 cc Maxlife

## Standard Kits

	E-Flo 4000	E-Flo 3000	E-Flo 2000
UHMWPE piston seal kit	277358	277362	277360
UHMWPE/Leather throat seal kit	277357	277357	277357
Chromex piston rod	15H280	15H280	15H280
Maxlife piston rod	15H589	15H589	15H589
Chrome cylinder	15G882	183048	183047
Maxlife cylinder	15H451	15H453	15H452

## Lowers

	E-Flo 4000	E-Flo 3000	E-Flo 2000
Stainless Steel Cromex	253522	253521	253520
Stainless Steel Maxlife	253525	253524	253523

## Manifold Assembly

	E-Flo 4000	E-Flo 3000	E-Flo 2000
Stainless Steel Cromex	15J749	15J748	15J747
Stainless Steel Maxlife	15J752	15J751	15J750

## Optional Kits

	E-Flo 4000	E-Flo 3000	E-Flo 2000
PTFE Piston Seal Kit	277359	277363	277361
PTFE Throat Seal Kit	239866	239866	239866
Leather throat seal kit	277356	277356	277356

## Accessories

<b>15H884</b> <b>Floor Stand</b> Durable floor stand to mount pump including mounting hardware	<b>15J423</b> Inlet/Outlet Fitting for 2" Tri-Clamp to 2" NPT
<b>15J753</b> <b>200/240 V Graco Programmed VFD kit</b> Kit includes programmed VFD, braking resistors, AppsLite module	<b>15J639</b> Inlet/Outlet Fitting for 2" Tri-Clamp to 1-1/2" Tri-Clamp
<b>15J754</b> <b>380/480 V Graco Programmed VFD kit</b> Kit includes programmed VFD, braking resistors, AppsLite module	<b>15J422</b> Inlet/Outlet Fitting for 1-1/2" Tri-Clamp to 1-1/2" NPT
<b>208997</b> <b>Back Pressure Regulator</b>	<b>15J755</b> Sensor Circuit Kit
<b>120373</b> <b>Local I/O Box</b> Local explosion proof pump control box	<b>288117</b> Pneumatic Back Pressure Regulator, 1-1/4" NPT
<b>15H885</b> <b>Ethernet Upgrade Kit</b> Kit enables Ethernet connection from the Graco supplied VFD.	<b>288262</b> Pneumatic Back Pressure Regulator, 2" Tri-Clamp
	<b>288311</b> Pneumatic Back Pressure Regulator, 1-1/2" NPT
	<b>288278</b> Gear Box Lubricant, 1 quart bottle
	<b>288414</b> Gear Box Lubricant, 12 pack carton

## Manuals

<b>311553</b> E-Flo operations manual	<b>311596</b> VFC manual
<b>311592</b> E-Flo installation manual	<b>311595</b> Pneumatic BPR manual
<b>311594</b> E-Flo repair parts manual	<b>311606</b> Pneumatic BPR/VFC manual