



# Graco Ink Pumps

Long-Lasting Piston Pumps with Sealed Wet Cup



Sealed Wet Cup



## Extend the service life of your pump

- Prolong seal life with enclosed, dual seal wet cup
- Runaway control with optional DataTrak™
- MaxLife® seal for longer life
- Handles the most difficult inks
- Available with hydraulic or pneumatic motors

**Springer Pumps, LLC**  
**Tel: 866-777-6060**  
**Fax: 866-777-6383**  
**info@springerpumps.com**  
**www.SPRINGERPUMPS.com**

PROVEN QUALITY. LEADING TECHNOLOGY.

## Technical Specifications

Stroke length .....	Pneumatic: 4.75 in (120.65 mm) Hydraulic: 4.69 in (119.13 mm)
Maximum fluid operating temperature .....	180° F (82.3° C)
Air or Hydraulic Inlet Size .....	3/4 npt (f)
Fluid outlet size .....	200 cc displacement pump: 1 npt (f) 500 cc displacement pump: 1-1/2 npt (f)
Maximum pump speed.....	60 cpm
(Do not exceed maximum recommended speed of fluid pump, to prevent premature pump wear)	



### DataTrak™


- Provides runaway pump protection
- Allows for real time monitoring for preventative maintenance

Ink Pump Package		Ratio	Remote		Power Source	Displacement Pump Size	Maximum Air or Hydraulic Input Pressure psi (MPa, bar)	Maximum Fluid Working Pressure psi (MPa, bar)
Part No.	Series		DataTrak	DataTrak				
258744	A	14:1			Air	500 cc	100 (0.7, 7.0)	1400 (9.7, 97)
258745	A	14:1	x		Air	500 cc	100 (0.7, 7.0)	1400 (9.7, 97)
258746	A	14:1		x	Air	500 cc	100 (0.7, 7.0)	1400 (9.7, 97)
258747	A	23:1			Air	200 cc	100 (0.7, 7.0)	2300 (15.9, 159)
258748	A	23:1	x		Air	200 cc	100 (0.7, 7.0)	2300 (15.9, 159)
258749	A	23:1		x	Air	200 cc	100 (0.7, 7.0)	2300 (15.9, 159)
258750	A	26:1			Air	500 cc	100 (0.7, 7.0)	2600 (17.9, 179)
258751	A	26:1	x		Air	500 cc	100 (0.7, 7.0)	2600 (17.9, 179)
258752	A	26:1		x	Air	500 cc	100 (0.7, 7.0)	2600 (17.9, 179)
258753	A	1.6:1			Hydraulic Oil	500 cc	1500 (10, 103)	2300 (15.9, 159)

## King™ Air Motor Conversion Kits

Part No.	Description
24C743	To install an L200CM Check-Mate displacement pump on an existing King air motor
24C744	To install an L500CM Check-Mate displacement pump on an existing King air motor

## ADDITIONAL INK SOLUTIONS



Viscount® II 3100  
on 55 gallon RAM



President® 10:1  
450 Cart Mount



Husky™ 307  
3/8 inch Pump



Husky 515  
1/2 inch Pump



Husky 1050  
1 inch Pump Family

RAM PACKAGES

AIR-OPERATED DOUBLE DIAPHRAGM PUMPS

All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Springer Pumps, LLC

861 Tech Drive  
Telford, PA 18969

Tel: 866-777-6060  
Fax: 866-777-6060  
INFO@springerpumps.com  
www.SPRINGERPUMPS.com

