Liquid Meter
FMT 50 PP

New

Innovators
in Flow Technology

New – FLUX Liquid Meter Type FMT 50 PP

The cost effective interlocked wheel impeller in the measuring chamber guarantees a fast and safe filling process. Suitable for neutral, low viscosity, not flammable liquids in conjunction with our JUNIORFLUX pump.

Benefits:
User-friendly handling, 5-digit LCD-Display, indication of the subset and total (not resetable), fast and safe calibration.

Type	**FMT 50 PP**
Flowrate	5-50 l/min
Operating pressure at 20 °C	4 bar
Viscosity	max. 40 mPas (cP)
Operating temperature	– 10 °C up to max. + 50 °C
Accuracy (not calibrated)	± 2 %
Accuracy (calibrated)	± 1 %
Inlet-outlet connections	Inlet G 1 (BSP 1"), outlet G 1A (BSP 1" male)
Material: housing	Polypropylene (PP)
Material: seal	FKM
Protection	IP 65
Weight	0,3 kg
Part No.	**A05 00 003**

Please ask for more information on FLUX liquid meters and details on our laboratory and barrel pump JUNIORFLUX. We would be glad to send you a detailed catalogue.

FMT 048/3 EFA

Springer Pumps, LLC
Tel: 866-777-6060 Fax: 866-777-6383 info@springerpumps.com www.springerpumps.com